

2/2 032

UNCLASSIFIED

PROCESSING DATE--20NOV70

CIRC ACCESSION NO--AP0127651

ABSTRACT/EXTRACT--(U) GP-C- ABSTRACT. THE TRANSVERSE MAGNETORESISTANCE (ANISOTROPY AND FIELD DEPENDENCES) AND HALL EFFECT IN A IRIIDIUM SINGLE CRYSTAL ARE INVESTIGATED AT LOW TEMPERATURES AND MAGNETIC FIELDS UP TO 45 KOE. THE MEASUREMENT RESULTS INDICATE THAT IRIIDIUM IS A "NONCOMPENSATED" METAL AND APPARENTLY POSSESSES A CLOSED FERMI SURFACE CONSISTING OF ELECTRON AND HOLE SHEETS. THE RESULTS ARE COMPARED WITH THE THEORETICAL MODEL OF THE FERMI SURFACE FOR THIS METAL.
FACILITY: INSTITUT FIZIKI METALLOV, AKADEMII NAUK SSSR.

UNCLASSIFIED

1/2 040
UNCLASSIFIED
TITLE--RADIAL DISTRIBUTION OF THE PARAMETERS OF THE PLASMA IN A PLANE
THERMIONIC ENERGY CONVERTER -U-
AUTHOR--(03)--DYUZHEV, G.A., STARTSEV, YE.A., YURVEV, V.G.
PROCESSING DATE--13NOV70
COUNTRY OF INFO--USSR
SOURCE--ZHURNAL TEKHNIЧЕСКОИ ФИЗИКИ, VOL 40, FEB 1970, P 426-428
DATE PUBLISHED--FEB70
SUBJECT AREAS--PHYSICS, ENERGY CONVERSION (NON-PROPULSIVE)
TOPIC TAGS--DISTRIBUTION THEORY, THERMIONIC ENERGY CONVERSION, RADICAL
FLOW, PLASMA DYNAMICS, ELECTRONIC SHIELDING, CURRENT DENSITY, CATHODE,
CESIUM PLASMA
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1979/1555
STEP NO--UR/0057/70/040/000/0426/0428
CIRC ACCESSION NO--AP0047883
UNCLASSIFIED

2/2 040

CIRC ACCESSION NO--AP0047883
ABSTRACT/EXTRACT--(U) GP-0-

UNCLASSIFIED

PROCESSING DATE--13NOV70

ABSTRACT. INVESTIGATION OF THE RADIAL DISTRIBUTION OF PLASMA PARAMETERS FOR THERMIONIC CONVERTERS WITH AND WITHOUT ELECTRODE (CATHODE AND ANODE) SHIELDING BY PLANE SAPPHIRE RINGS. IT IS SHOWN THAT FOR CURRENTS RANGING FROM 2 TO 15 A-SQ CM, THE BOLTZMANN FORMULA HOLDS FOR LOW AND HIGH CESIUM PRESSURES. ELECTRODE SHIELDING DOES NOT EFFECT THE RADIAL DISTRIBUTION OF THE PLASMA PARAMETERS, AND DOES NOT DIMINISH THE EDGE EFFECT ASSOCIATED WITH THE RADIAL DIFFUSION OF CARRIERS FROM THE GAP. HOWEVER, SHIELDING HAS THE EFFECT OF APPRECIABLY REDUCING THE INFLUENCE OF THE LATERAL SURFACE OF THE CATHODE, WHICH OTHERWISE WOULD EMIT ELECTRONS INTO THE PLASMA. THIS MEANS THAT THE TRUE ELECTRON CURRENT DENSITY CANNOT BE RELIABLY DETERMINED WITHOUT ELECTRODE SHIELDING.

UNCLASSIFIED

USSR

UDC 535.37

KAS'KOV, B. N., KATIBNIKOV, M. A. and STARTSEV, YU. V.

"Spectral-Luminescence Study of the Interaction of Compounds of High Molecular Weight With Dyes. 1. Interaction of Acridine Orange and Acridine Yellow with Polymethacrylic Acid"

Vestn. Belorus. un-ta (Herald of Belorussian University), 1971, Series 1, No 1, pp 30-33 (from RZh-Fizika, No 7, Jul 71, Abstract No 7D758)

Translation: The effect of additions of various concentrations of polymethacrylic acid on the absorption and fluorescence spectra and also on the degree of polarization of the fluorescence of aqueous solutions of acridine orange and acridine yellow were studied. A comparative study of the spectral characteristics and vector characteristics of the emission showed the role of individual centers in the mechanism for the complex formation of dyes with a polyelectrolyte. It was shown that the optical effects observed in the adsorption and fluorescence spectra and the degrees of polarization of the fluorescence are associated with the formation of joint aggregates of the dye with polymers of various structures. 12 ref. Authors abstract.

1/1

USSR

MAGZUNOV, B. Kh., SAIYANTS, T. I., TYUTINA, V. A., STARTSEVA, L. I., and GILMANOVA, G. A., Chair of Social Hygiene and Public Health Organization, Tashkent Medical Institute

"Study of Basic Cardiovascular Diseases in Tashkent From a Sociosanitary Aspect"

Tashkent, Meditsinskiy Zhurnal Uzbekistana, No 10, Oct 70, pp 39-44

Abstract: The voluminous statistical data on the death rate due to cardiovascular diseases in the Soviet Union indicate that these diseases are the number-one killers. Not only medical but also sociohygienic and socioeconomic measures must be taken to combat this set of diseases; however, the etiology, pathogenesis, and treatment have not yet been studied in detail. A study was made of the characteristics of cardiovascular diseases in relation to work and living conditions, characteristics of the spread of cardiovascular pathology in nosological forms, and analysis of cardiovascular diseases with time loss in work capacity, disability, and death. Data from the medical-prophylactic records in Tashkent were used. Data on workers from various Tashkent industries were included. Among this group
1/2

USSR

MAGZUMOV, B. Kh., et al, Meditsinskiy Zhurnal Uzbekistana, No 10, Oct 70, pp 39-44

7.8% had cardiovascular diseases. Hypertension was found most frequently in women. Those in sedentary occupations requiring little physical exercise were more susceptible to hypertension than those engaged in physical work. As a result of this study, it was recommended that steps be taken to combat rheumatic fever, influenza, and other infectious diseases, to specifically treat those who live and work under conditions which promote cardiovascular disease, and to carry out sanitary-educational work in the field of cardiovascular diseases.

2/2

- 94 -

1/2 014 UNCLASSIFIED PROCESSING DATE--13NOV70
TITLE--P, HYDROXY SUBSTITUTED BENZENES. X. ULTRAVIOLET SPECTRA OF SOME
P, HYDROXYAZOBENZENE DERIVATIVES -U-
AUTHOR--(02)--STARTSEVA, N.V., FRANKOVSKIY, CH.S.
COUNTRY OF INFO--USSR
SOURCE--ZH. ORG. KHIM. 1970, 6 (5), 1032-5
DATE PUBLISHED-----70
SUBJECT AREAS--CHEMISTRY
TOPIC TAGS--BENZENE DERIVATIVE, ORGANIC AZO COMPOUND, HYDROXY RADICAL, UV
SPECTRUM, CHLORINATED ORGANIC COMPOUND, AMINE DERIVATIVE, AROMATIC
AMINE, AROMATIC CARBOXYLIC ACID, PHENOL, BROMINATED ORGANIC COMPOUND
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--3006/1280 STEP NO--UR/0366/70/006/005/1032/1035
CIRC ACCESSION NO--AP0134954
UNCLASSIFIED

2/2 014

CIRC ACCESSION NO--AP0134954

UNCLASSIFIED

PROCESSING DATE--13NOV70

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. UV SPECTRA WERE REPORTED ON 2,4,RR
PRIME1 C SUB6-H SUB3 N: NO SUB6 H SUB4 R PRIME2 -4 (I) (R, R PRIME1, AND
R PRIME2 GIVEN): H, H, OH; H, NO SUB2, OH; H, CL, OH; H, CO SUB2 ET, OH;
CL, H, OH; CL, NO SUB2, OH; CL, CO SUB2 ET, OH; CL, CN, OH; CL, SCN, OH;
H, H, NO SUB2; H, H, CN; H, H, AC; H, H, H; H, H, NH SUB2; H, H, NME
SUB2; H, NH SUB2, NO SUB2; H, OH, NO SUB2; H, NME SUB2, NO SUB2; CL,
ONE, OH; CL, ME, OH; CL, CL, OH; CL, BR, OH; CL, NHAC, OH; CL, I, OH;
AND CL, CO SUB2 H, OH. THE TRANSFER OF ELECTRONIC CHARGE THROUGH I
CHROMOPHORE IS 3-5 TIMES WEAKER THAN THROUGH THE CORRESPONDING PHENOL
SYSTEM. THE WAVE NOS. OF THE UV MAX. WERE CORRELATED WITH HAMMETT SIGMA
CONTS.

UNCLASSIFIED

009
UNCLASSIFIED
TITLE--SYNTHESIS AND PYROLYSIS OF CYCLOBUTYLMETHYL TRIMETHYLSILANE -U-
PROCESSING DATE--30OCT70
AUTHOR--(05)-NAMETKIN, N.S., GUSELNIKOV, L.YE., USHAKOVA, R.L., STARTSEVA,
O.M., VDOVIN, V.M.
COUNTRY OF INFO--USSR
SOURCE--IZV. AKAD. NAUK SSSR, SER. KHIM. 1970, (2), 494-6
DATE PUBLISHED-----70
SUBJECT AREAS--CHEMISTRY
TOPIC TAGS--CHEMICAL-SYNTHESIS, PYROLYSIS, ORGANIC SILANE, PLATINUM
COMPOUND, CATALYST
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1997/0847
CIRC ACCESSION NO--AP0119751
STEP NO--UR/0062/70/000/002/0494/0496
UNCLASSIFIED

2/2 009

UNCLASSIFIED

PROCESSING DATE--30OCT70

CIRC ACCESSION NO--AP0119751

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. ADDING 15.5 G METHYLENECYCLOBUTANE
OVER 2 HR TO 23 G ME SUB2 SIHCl AND 0.2 ML H SUB2 PTCI SUB6 CATALYST IN
THF, AND HEATING THE MIXT. 8 HR AT 110DEGREES GAVE 51PERCENT
DIMETHYL(CYCLOBUTYLMETHYL) CHLOROSILANE, B. 167-8DEGREES, N PRIME20 SUBD
1.4465, D PRIME20 0.9296. THIS WITH MEMGI GAVE 55.4PERCENT
(CYCLOBUTYLMETHYL) TRIMETHYLSILANE, B. 145DEGREES, 1.4310, 0.7816.
PYROLYSIS IN A STATIC SYSTEM AT 430DEGREES GAVE 51PERCENT CH SUB2:CHCH
SUB2 SIME SUB3 IN 30 MIN. IN AN IMPULSE PYROLYSIS AT 575DEGREES WITH 12
SEC CONTACT TIME, 61PERCENT CONVERSION WAS ATTAINED; THE AMT. OF SAMPLE
DID NOT AFFECT THE CONVERSION, SHOWING THAT THE REACTION IS TRULY
MONOMOL. AND FORMS THE ABOVE PRODUCT AND C SUB2 H SUB4.
FACILITY: INST. NEFTEKHIM.SIN. IM. TOPCHIEVA, MOSCOW, USSR.

UNCLASSIFIED

Refractory Materials

USSR

UDC 669.01:666.76.001.5

KHARCHENKO, I. G., SAZHIN, V. A., STARUN, V. R., RADCHENKO, I. I., TANDURA, I. P., and KOVALENKO, A. N.

"Some Problems of Internal Heat Exchange During Roasting of Magnesians Refractories"

Dnepropetrovsk, Metallurgicheskaya i Gornorudnaya Promyshlennost', No 4, Jul-Aug 70, pp 49-51

Abstract: Experimental material on the effect of the heating rate of the heat-and mass-transfer processes on the thermophysical parameters of roasted refractories is summarized. The material, published for the first time in the Soviet literature, can be used as a basis for further studies for determination of effective methods of heat treatment of magnesians refractories.

PHYSICS

Acoustics

USSR

SABIROV, L. M., STARUNOV, V. S., and FABELINSKIY, I. L., Physics Institute imeni P. N. Lebedev, USSR Academy of Sciences.

"Determining the Velocity and Absorption of Hypersound in Viscous Liquids: From Scattered-Light Spectra"

Moscow, Zhurnal Eksperimental'noy i Teoreticheskoy Fiziki, Vol 60, No 1, 1971, pp 146-159

Abstract: Using gas lasers, either with an Ne-He mixture, $\lambda = 6328 \text{ \AA}$ (40 mw), or a He-Cd114 mixture, $\lambda = 4416 \text{ \AA}$ (20 mw), and working in a multimode operation to excite scattered light, the authors experimentally studied the fine structure of the extremities of the Rayleigh line in salol and benzophenone, with the viscosities varying by many orders of magnitude. The phenomenon of the fine structure of the extremities of the Rayleigh line results from the fact that a doublet is observed in the spectra of depolarized scattered light under specific conditions. The velocity and absorptivity of longitudinal hypersound were determined in salol, benzophenone, and triacetate over a broad viscosity range. Two branches of transverse hypersound oscillations in liquids were observed. --- low temperature ("normal"), 1/2

USSR

SABIROV, L. M., et al, Zhurnal Eksperimental'noy i Teoreticheskoy Fiziki, Vol 60, No 1, 1971, pp 146-159

in which the transverse components in the scattered-light spectra are shifted with decrease in temperature, and the high-temperature ("anomalous") branch, in which these components draw closer together with temperature decrease. The temperature range used was -65 to $+137^{\circ}$ C. The theory that the scattering of anisotropy fluctuations is characterized by two relaxation times most fully explains the experimental findings.

2/2

- 25 -

USSR

STARUNOV, V. S., FABELINSKIY, I. L.

UDC 621.375.82

"Thermal and Induced Molecular Scattering of Light"

V sb. Sovrem. probl. fiz. khimii (Modern Problems of Chemical Physics -- Collection of Works), Vol. 5, Moscow, Moscow University, 1970, pp 174-203 (from RZh-Fizika, No 7, Jul 71, Abstract No 7D993)

Translation: A survey is presented covering studies of thermal and induced molecular scattering of light. 79 ref.

1/1

1/2 039 UNCLASSIFIED PROCESSING DATE--27NOV70
TITLE--INDUCED ENTROPY, TEMPERATURE, SCATTERING OF LIGHT IN LIQUIDS -U-

AUTHOR-(03)-KYZYLASOV, YU.I., STARUNOV, V.S., FABELINSKIY, I.L.

COUNTRY OF INFO--USSR

SOURCE--PIS'MA ZH. EKSP. TEOR. FIZ. 1970, 11(2), 110-13

DATE PUBLISHED-----70

SUBJECT AREAS--PHYSICS

TOPIC TAGS--ENTROPY, LIGHT SCATTERING, BENZENE, ETHANOL, RUBY LASER, FABRY
PEROT INTERFEROMETER

CONTROL MARKING--NO RESTRICTIONS

DOCUMENT CLASS--UNCLASSIFIED

PROXY REEL/FRAE--1994/0998

STEP NO--UR/0386/70/011/002/0110/0113

CIRC ACCESSION NO--AP0115019

UNCLASSIFIED

UNCLASSIFIED

PROCESSING DATE--27NOV70

2/2 039

CTRC ACCESSION NO--AP0115019

ABSTRACT/EXTRACT--(U) GP-O- ABSTRACT. A STOKES SHIFTED LINE OF INDUCED ENTROPY SCATTERING OF LIGHT WAS OBSD. IN LIQS.; THE SCATTERING WAS CAUSED BY THE ELECTROCALORIC EFFECT. THIS SCATTERING WAS EXCITED IN C SUB6 H SUB6 AND ETOH BY A LIGHT PULSE (10-15 NSEC) OF A RUBY LASER (MAX. OUTPUT SIMILAR TO 180 MW, LINE WIDTH 2-3 TIMES 10 PRIME NEGATIVE2 CM PRIME NEGATIVE1). THE LIGHT, SCATTERED UNDER AN ANGLE OF 90DEGREES, WAS ANALYZED BY A FABRI-PEROT INTERFEROMETER. THE STOKES SHIFTS WERE OF SIMILAR TO 10 PRIME NEGATIVE2 CM PRIME NEGATIVE1. BY ADDING AN ABSORBENT TO THE LIQS., AN ANTI STOKES SHIFTED LINE OF INDUCED TEMP. SCATTERING OCCURRED. AT HIGH ABSORPTIVITIES AND INTENSITIES OF EXCITING RADIATION, THE ANTI STOKES SHIFT WAS SEVERAL TIMES HIGHER THAN THE STOKES ONE. IN THE CASE OF C SUB6 H SUB6, THE STOKES AND ANTI STOKES (OWING TO THE EFFECT OF NONLINEAR LIGHT ABSORPTION) SHIFTS WERE OBSD. AT THE OUTPUTS OF SIMILAR TO 50-80 AND LARGER THAN 80 MW, RESP.

FACILITY: FIZ. INST., IM. LEBEDEVA, MOSCOW, USSR.

UNCLASSIFIED

1/2 019
UNCLASSIFIED
PROCESSING DATE--04DEC70
TITLE--STIMULATED ENTROPY TEMPERATURE SCATTERING OF LIGHT IN LIQUIDS -U-
AUTHOR-(04)-KYZYLASOV, YU.P., STARUNOV, V.S., FABELINSKIY, I.L., LEBEDEV,
P.N.
COUNTRY OF INFO--USSR
SOURCE--JETP LETTERS (USA), VOL. 11, NO. 2, P. 110-13 (JAN. 1970)
DATE PUBLISHED-----70
SUBJECT AREAS--PHYSICS
TOPIC TAGS--LIGHT SCATTERING, ENTROPY
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--3007/1090
STEP NO--US/0000/70/011/002/0110/0113
CIRC ACCESSION NO--AP0136510
UNCLASSIFIED

2/2 019

UNCLASSIFIED

PROCESSING DATE--04DEC70

CIRC ACCESSION NO--AP0136510

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. INVESTIGATIONS HAVE SHOWN THAT STIMULATED (ENTROPY) SCATTERING OF LIGHT (STS) CAN BE DUE TO TWO DIFFERENT CAUSES. IT FOLLOWS FROM A GENERAL ANALYSIS OF THE STS PHENOMENON THAT THE STS LINE DUE TO THE ELECTROCALORIC EFFECT SHOULD BE SHIFTED TO THE STOKES SIDE RELATIVE TO THE FREQUENCY OF THE EXCITING RADIATION (STS-I), AND THE STS LINE DUE TO THE DIRECT ABSORPTION OF LIGHT SHOULD HAVE AN ANTI STOKES SHIFT (STS-II). THE AUTHORS REPORT HERE THE FIRST OBSERVATION OF THE STS-I LINE IN LIQUIDS, WITH AN INTENSITY MAXIMUM SHIFTED IN THE STOKES DIRECTION RELATIVE TO THE FREQUENCY OF THE EXCITING RADIATION. THEY HAVE THUS OBSERVED THE STS DUE TO THE ELECTROCALORIC EFFECT. IN THERMAL (SPONTANEOUS) SCATTERING, THIS FORM OF STS CORRESPONDS TO SCATTERING OF LIGHT BY ENTROPY FLUCTUATIONS. FACILITY: USSR ACAD. SCIS.

UNCLASSIFIED

USSR

UDC 621.317.8

SPIVAK, N. D., STARUSH, E. G., TSETENS, V. P.

"On the Cold Resistance of Microwire Resistors Made From Nickel-Based Alloy"

V sb. Mikroprovod i pribory soprotivl. (Microwire and Resistance Devices --collection of works), Vyp. 7, Kishinev, 1971, pp 147-152 (from RZh-Radiotekhnika, No 8, Aug 71, Abstract No 8V354)

Translation: In order to determine the effect which repeated cold cycles have on resistors made from M94 and M95 nickel-base alloys developed by Ye. Ya. Badinter and A. L. Gadolin, they were cooled to a temperature of -60°C and held at this temperature for 4 hours. It was found from the results of the tests that resistors based on these alloys are 10-20 times as resistant to cold as similar resistors made from manganin microwire, which is extensively used for making microwire resistors. At the same time, the stability of "M" resistors with respect to climatic and mechanical effects is on a level with that of type MVSG resistors made from manganin-based microwire. Bibliography of three titles. Ye. M.

1/1

- 189 -

AND0012621

5

UR 9021

TITLE-- CAPTION

NEWSPAPER-- SOVetskaya Moldaviya, January 8, 1970, P 1, COLS 5-6

ABSTRACT-- A PHOTOGRAPH SHOWS I. G. STANISH, SENIOR ASSOCIATE, AND B. K. ZALEVSKIY, ASSOCIATE, CALIBRATING A VACUUM THERMAL MANOMETER AT THE KISHENEV SCIENTIFIC-RESEARCH INSTITUTE FOR DESIGN OF ELECTRICAL DEVICES /NAUCHNO-ISSLEDOVATEL'SKIY INSTITUT ELEKTRO-PRIBOROSTROYENIYA/.

12
5
1
8
LW

1/1

21

19571515

USSR

UDC: 621.791.052.011:539.3

YUSHCHENKO, K. A., MAKHNENKO, V. I., and STARUSHCHENKO, Institute of Electric Welding
imeni Ye. O. Paton, Academy of Sciences Ukrainian SSR

"Thermal Stresses in the Welded Joints of Invar and Stainless Steel at Cryogenic
Temperature"

Kiev, Avtomaticheskaya Svarka, No 10, Oct 73, pp 27-29

Abstract: The authors use computational methods and the Minsk-22 computer to study the distribution of thermal stresses in the welded joints of pipes made from Invar, and Invar and the following types of stainless steel: OKH18N1OT and OOKH2QN16AG6. Increasing the coefficient of thermal expansion of the seam metal up to $\alpha = 4-5 \times 10^{-6}$ degree⁻¹ in the welded joints of Invar results in an insignificant increase in thermal stresses for temperature changes in the $4-293^{\circ}\text{K}$ interval. Significant stresses arise in the welded joint at $\alpha = 10-12 \times 10^{-6}$ degree⁻¹. The use of the KH18N1OT type material as an addition agent is not desirable in the welded joints of pipelines made from 36N grade alloy, where the pipelines operate under conditions of cyclical temperature change within the $4-293^{\circ}\text{K}$ limits (without taking into consideration the application of external loads). Instead, 36NGMT filler wire should be used. When using 36NGMT for welding the following materials, which have to operate at temperature changes at low

1/2

.USSR

YUSHCHENKO, K. A., et al, Avtomaticheskaya Svarka, No 10, Oct 73, pp 27-29
temperatures, the welding has to be carried out carefully: 36N-KH18N10T, 36N-
000KH20-N16AG6. The stresses are evoked by differences in the coefficients of
thermal expansion during thermal changes within the 4-293°K interval.

2/2

- 56 -

172 022
UNCLASSIFIED
TITLE--DYNAMICS OF THE LIVER TISSUE PROTEINS IN CONNECTION WITH FORMATION
OF WATER ELECTROLYTIC BILE FRACTION -U-
AUTHOR--(03)--ESIPENKO, B.E., STARUSHENKO, L.I., KOSTROMINA, A.P.
COUNTRY OF INFO--USSR
SOURCE--FIZIOLOGICHNIY ZHURNAL, 1970, VOL 16, NR 3, PP 336-340
DATE PUBLISHED-----70
SUBJECT AREAS--BIOLOGICAL AND MEDICAL SCIENCES
TOPIC TAGS--LIVER, BILE, ELECTROPHORESIS, WATER METABOLISM, POTASSIUM
COMPOUND, SODIUM COMPOUND
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1994/1360
CIRC ACCESSION NO--AP0115331
STEP NO--UR/0238/70/016/003/0336/0340
UNCLASSIFIED

022
CIRC ACCESSION NO--AP0115331 UNCLASSIFIED
ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THE CONTENTS OF PROTEINS AND
ELECTROFORETIC FRACTIONS QUANTITY OF WATER AND ELECTROLYTES WERE
STUDIED IN THE LIVER TISSUE AND BILE AT DIFFERENT LEVELS OF BILIFICATION
CONDITIONED BY THE STATE OF WATER SALT METABOLISM. A PRONOUNCED
DEPENDENCE WAS FOUND OF PROTEIN CONTENT IN THE LIVER TISSUE ON THE STATE
OF WATER SALT METABOLISM IN THE ORGANISM. WHEN THE ORGANISM IS
OVERSATURATED WITH WATER, THE CONTENT OF TOTAL PROTEIN INCREASE BY
13PERCENT AND THAT OF "B" FRACTIONS OF WATER SOLUBLE PROTEINS IN THE
LIVER TISSUE BY 40PERCENT. WITH AN INCREASE OF "B" FRACTION CONTENT IN
THE LIVER TISSUE BY 1PERCENT THE AMOUNT OF POTASSIUM IN THE LIVER TISSUE
RISES BY 24.6 SODIUM, BY 13.06 MEQ-KG OF RAW TISSUE, THE LEVEL OF
BILIATION, BY 2.72 ML-MIN KG, SODIUM IN BILE BY 0.449 MEQ-MIN KG. A
MORE CONSIDERABLE EXCRETION OF POTASSIUM WITH BIL CORRESPONDS TO A
HIGHER CONTENT OF TOTAL PROTEIN IN THE LIVER TISSUE. THE OBTAINED
RESULTS MAKE IT POSSIBLE TO CONSIDER THAT WATER SOLUBLE PROTEINS OF "B"
FRACTIONS PLAY AN IMPORTANT ROLE IN THE FORMATION OF WATER ELECTROLYTIC
BILE FRACTION. FACILITY: DEPARTMENT OF METABOLISM PHYSIOLOGY,
THE A. A. BOGOMOLETZ INSTITUTE OF PHYSIOLOGY, ACADEMY OF SCIENCES,
UKRAINIAN SSR.

PROCESSING DATE--16OCT70

UNCLASSIFIED

USSR

UDC 621.791:669.245

YUSHCHENKO, K. A., KAKHOVSKIY, N. I., and STABISHENKO, T. M., Institute of Electric Welding imeni Ye. O. Paton; IL'ICHEV, V. YA., Physicotechnical Institute of Low Temperatures, Academy of Sciences Ukrainian SSR; ZAKHAROV, A.I., Central Scientific Research Institute of Ferrous Metallurgy

"Weldability and Properties of Invar Weld Joints at Low Temperatures"

Kiev, Avtomaticheskaya Svarka, No 9, Sept 72, pp 39-42

Abstract: The purpose of this investigation was to develop the technology of welding Fe-Ni alloys (36N, 36NKh, and 39N) with a thickness up to 5 mm and to evaluate the weldability of Invar with a thickness up to 12 mm in order to obtain a strong and dense joint with the required mechanical and thermophysical properties in the 20 to -253°C interval. Chemical composition of the Fe-Ni alloys was (in %):

	C	Si	Mn	S	P	Ni	Cr
36N	0.032	0.23	0.43	0.009	0.008	36.1	----
36NKh	0.035	0.15	0.52	0.004	0.004	37.0	0.49
36N	0.034	0.19	0.50	0.008	0.009	39.9	----

Samples were submerged-arc welded with a nonconsumable tungsten electrode in argon, both with filler wire and without it, with AN-26 and AnF-5 fluxes.

1/2

YUSHECHENKO, K.A., et al., *Avtomaticheskaya Svarka*, No 9, Sep 72, pp 39-42

Low-temperature studies of the weld joints were carried out at the physicochemical Institute of Low Temperatures, Academy of Sciences Ukrainian SSR, the Central Scientific Research Institute of Ferrous Metallurgy, and the Institute of Electric Welding. Analysis of the mechanical and thermophysical properties of weld joints at low temperatures where 36NGT, 36NGTce, and 36NGCce filler wires were used showed that alloying with Ti and Mn produces a dense joint where the alloy strength is equal to that of the base metal of the seam and possesses high impact strength and ductility at -253°C . Experimental studies of welded Invar (6 and 12 mm thick) showed that the use of 36NGT filler wire yields seams with defects (hot cracks). 6 figures, 2 tables, 8 bibliographic references.

2/2

- 43 -

Acc. Nr.: AP0029105

PRIMARY SOURCE: Zhurnal Nevropatologii i Psikhatrii, 1970,
Vol 70, Nr 1, pp 122-125

Ref. Code: UR 0246

THE MECHANISM OF ACTION AND THERAPEUTIC EFFECT
OF ELENIUM AND DUXEN IN DIENCEPHALIC EPILEPSY

Gromov, S. A.; Starykh, N. T.

A pharmacological study of Elenium displayed that this preparation does not possess a peripheral and central adrenoblocking action, as well as a M and N cholinergic activity. In other words, it does not affect the vegetative nervous system. In treating 117 patients with diencephalic epilepsy by Elenium and Duxen a high therapeutical effectivity was definitely marked. A stable improvement was attained in 83-85% of the cases. Satisfactory results were seen in 7-9% of the cases. In 6-10% there were no changes. A suspension in the use of these drugs brought on a renewal of diencephalic attacks. The authors presume that the therapeutical effect of these preparation is achieved by a possible block of the pathological stimuli on the level of the thalamus, limbic system and deep areas of the temporal lobe.

REEL/FRAME

19680616

MB

2

USSR

UDC 620.179.118

MOISEYEV, L. M., STARYY, I. B., and KHANONKIN, A. A., Odessa State Pedagogical Institute

"Method of Studying the Wrinkled Microrelief Occurring on the Surface of a Cyclic-Strained Single Crystal"

Metallofizika, Resp. mezhved. sb. (The Physics of Metals. Republic Interdepartment Collection of Works), 1970, vyp. 29, pp 177-180 (from RZh-Metallurgiya, No 3, Mar 71, Abstract No 31885 by authors)

Translation: The established fact of the appearance of a wrinkled microrelief on the surface of Al single crystal as a result of its cyclic straining is used as the basis for suggesting a method of studying this microrelief, based on the phenomenon of x-ray automagnification. A loading method is suggested which permits continuous bending of the Al single crystal and, if necessary, its cyclic straining. The x-ray optical scheme of the experiment makes it possible to obtain reflexograms, with which it is possible to study the distribution of wrinkles on the crystal surface and its dynamics in relation to the number of loading cycles. Three illustrations. Bibliography with nine titles.

1/1

- 36 -

USSR

UDC 539.23:539.25

STARVY, I. B. and CHEPOK, O. L., Odessa Pedagogical Institute imeni
K. D. Ushinskiy

"Investigation of the Structure of Chromium Silicide Thin Films Condensed on
Preheated Substrate"

Kiev, Metallofizika, No 40, 1972, pp 56-59

Abstract: It was established that in the investigated temperature interval of condensation (300-1020° C) there exists a region of temperatures where the condensation mechanism of the vaporamorphous phase system changes by a mechanism of heterogeneous condensation. The activation energies of the processes of Si-Cr film structure formation were determined. It was established that the temperature of film contact with the air after condensation determines the degree of system dispersity. 2 figures, 7 bibliographic references.

1/1

USSR

Waveguides

UDC: 621.372.81

KOROZA, V. I. and STARZHINSKIY, V. M.

"Oscillation Theory Methods in Waveguide System Electrodynamics"

Moscow, Vestnik Moskovskogo Universiteta--Matematika, Mekhanika, No 1, 1971,
pp 101-110

Abstract: This article, presented at a seminar of the Moscow State University Department of Applied Mechanics, 19 November 1969, demonstrates how the theory of oscillations can be applied to some problems of wave propagation in a solid medium if these problems can be approximated by systems with a finite number of degrees of freedom. Specific consideration is given to the problem of wave propagation in periodic electromagnetic waveguides. The authors begin their analysis by considering a three-dimensional region containing a section of the rectilinear z axis, with the boundaries of the region as a metallic surface and two planes parallel to the xy plane. The further assumption is made that all possible cross sections of the given region are simply connected with and bounded by the planes $z = \text{const}$. It is stipulated that the field components of the electromagnetic wave vary with time according to the harmonic law, when the problem of computing the field at a given frequency reduces to finding the complex amplitudes of the electric and magnetic fields.

1/1

USSR

UDC 678.01:539.376

SVIRIDENOK, A. I., STARZHINSKIY, V. Ye., and ZHULEGO, V. T., Institute of the Mechanics of Metal-Polymer Systems, Academy of Sciences, Belorussian SSR

"Some Engineering Applications of Contact Problems in the Theory of Visco-elasticity"

Minsk, Izvestiya Akademii Nauk BSSR, Seriya Fiziko-Tekhnicheskikh Nauk, No 1, 1972, pp 57-65

Abstract: In this article, which deals with some engineering applications of contact problems, an effort is made to provide a solution of a contact problem for linear viscoelastic solids of the simplest shape (a sphere, a cylinder). To describe the process of change of the contact parameters with respect to time, there has been selected a law of deformation in differential form with an exponential time function. Calculation relationships are presented for determination of the contact parameters. Satisfactory coincidence of the experimental and calculation data is obtained. 2 figures, 32 bibliographic entries.

1/1

- 49 -

USSR

UDC: 539.1.07

MARKOV, K. P., RYABOV, N. V., STAS', K. N.

"Use of Photographic Films for Individual Radiometry of the Daughter Products of Radon"

Tr. Soyuzn. n.-i. in-ta priborostr. (Works of the Union Scientific Research Institute of Instrument Building), 1970, vyp. 12, pp 184-191 (from RZh-Metrologiya i Izmeritel'naya Tekhnika, No 11, Nov 70, Abstract No 11.32.1471)

Translation: The authors consider the possibility of individual monitoring for the atmospheric content of radon decay products according to the "latent" energy by pumping air through a filtering cloth while simultaneously using a ZnS(Ag) scintillator and a photographic film to register the α -activity of the specimen. The paper gives the results of theoretical and experimental studies on determining the sensitivity of the method and the measurement range.

1/1

1/2 011
UNCLASSIFIED
PROCESSING DATE--27NOV70
TITLE--ON THE MECHANISM OF POROUS STRUCTURE FORMATION IN SILICA GELS,
EFFECT OF SILICIC ACID HYDROGEL AGEING IN ORGANIC SOLVENTS ON THE
AUTHOR--(03)--SHEYNFAYN, R.YU., STAS, O.P., NEYMARK, I.YE.
COUNTRY OF INFO--USSR
SOURCE--KOLLOIDNYY ZHURNAL, 1970, VOL 32, NR 3, PP 451-453
DATE PUBLISHED-----70
SUBJECT AREAS--CHEMISTRY
TOPIC TAGS--POROSITY, SILICA GEL, ORGANIC SOLVENT, GEL
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--2000/2139
CIRC ACCESSION NO--AP0125722
STEP NO--UR/0069/70/032/003/0451/0453
UNCLASSIFIED

2/2 011
CIRC ACCESSION NO--AP0125722
ABSTRACT/EXTRACT--(U) GP-0-

UNCLASSIFIED

PROCESSING DATE--27NOV70

ABSTRACT. SOLUTIONS OF WATER SOLUBLE ORGANIC
SOLVENTS HINDER THE AGEING OF SILICI ACID HYDROGEL. UNLIKE WATER,
ORGANIC MEDIUM INHIBITS THE GROWTH OF HYDROGEL PARTICLES. THIS RESULTS
IN XEROGELS WITH HIGHLY DEVELOPED SURFACE AREA CORRESPONDING TO THE SIZE
OF FRESHLY PRECIPITATED HYDROGEL PARTICLES. STABILIZATION OF PARTICLES
IS ACCOUNTED FOR BY THE FORMATION AROUND THEM OF ADSORPTION SOLVATION
SHEATHS FROM ORGANIC MOLECULES WHICH HINDER THEIR GROWTH.
FACILITY: INSTITUT FIZICHESKOY KHIMII AN USSR, KIEV.

UNCLASSIFIED

USSR

UDC 541.182.644:541.183.7

SHEYNFAYN, R. YU., STAS', O. P., and NEYMARK, I. YE.

"Synthesis and Adsorption Properties of Mixed Adsorbents of the Type Silica gel -- Zeolite"

Leningrad, Zhurnal Prikladnoy Khimii, Vol 45, No 10, Oct 72, pp 2192-2195

Abstract: In studying the adsorption properties of the zeolite-silica gel type sorbents in relationship to their composition and methods of preparation, it was established that the mutual effect of both components of the mixture results in a deviation from additive value in the area of capillary vapor condensation. Macropores are formed when silica gel is brought in contact with zeolite. The volume of the macropores increases with increased quantity of the zeolite added. A method for the preparation of mixed adsorbents with different porous structures was developed based on mixing zeolite with zerosilo gel. The zeolite-silica gel obtained in this manner shows a bidisperse structure.

1/1

Acc. Nr:

AP0036536

Ref. Code: UR 0069

PRIMARY SOURCE: Kolloidnyy Zhurnal, 1970, Vol 32, Nr 1,
PP 104-108

ON THE MECHANISM OF POROUS STRUCTURE FORMATION IN SILICAGEL

CHANGE IN POROUS STRUCTURE OF SILICA GEL UNDER THE ACTION
OF HYDROFLUORIC ACID AT THE HYDROGEL AGEING STAGE

Stas', O. P.; Sheynfayn, R. Yu.; Neymark, I. Ye.

Summary

New possibilities have been found for the porous structure control in silica gels by treating hydrogel with HF. With higher HF concentrations and longer ageing times of hydrogel in it, the pore volume of silica gel increases and its surface area diminishes. A certain similarity has been discovered in the effect of HF and hydroxyl ions concentration on hydrogel ageing, viz. that the porous structure changes in xerogels obtained in the two cases are similar.

D. n.

REEL/FRAME
19721384

7

174 043
UNCLASSIFIED
TITLE--IRRADIATION AND ANNEALING OF P TYPE GERMANIUM -U-
AUTHOR--(02)-STAS, V.F., SMIRNOV, L.S.
COUNTRY OF INFO--USSR
SOURCE--FIZ. TEKH. POLUPROV. 1970, 4(2), 276-81
DATE PUBLISHED-----70
SUBJECT AREAS--PHYSICS
TOPIC TAGS--SILICON SINGLE CRYSTAL, GERMANIUM, CRYSTAL DEFECT, CRYSTAL
VACANCY, PLASTIC DEFORMATION, IRRADIATION EFFECT, ANNEALING
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1996/1866
CIRC ACCESSION NO--AP0118830
STEP NO--UR/0449/70/004/002/0276/0281
UNCLASSIFIED

2/2 048

CIRC ACCESSION NO--AP0118830
ABSTRACT/EXTRACT--(U) GP-0-

UNCLASSIFIED

PROCESSING DATE--27NOV70

ABSTRACT. GA DOPED P-SI CRYSTALS (5 AND 25 OHM CM) WITH A GROWTH DISLOCATION D. SIMILAR TO 10 PRIME3-CM PRIME2 AS WELL AS WITH DISLOCATIONS INTRODUCED BY PLASTIC DEFORMATION WERE INVESTIGATED. THE SAMPLES WERE IRRADIATED IN A PULSE ACCELERATOR BY 3.5 MEV ELECTRONS THEN ANNEALED ISOTHERMALLY OR ISOCHRONOUSLY. THE TEMP. DEPENDENCES OF THE HALL COEFF. AND OF COND. WERE MEASURED AT VARIOUS STAGES OF ANNEALING AND 80-400DEGREESK. THE TEMP. DEPENDENCE OF HOLE CONCN. IN THE 5 OHM CM SAMPLES INDICATES THAT A CENTER WITH A DONOR LEVEL E SUBV PLUS 0.07 EV IS INTRODUCED DURING ANNEALING AT 170DEGREESK. THE 0.07 EV LEVEL IN THE 5 OHM CM SAMPLES CANNOT FULLY DISAPPEAR DURING ANNEALING EVEN AT 400DEGREESK. THE ISOCHRONOUS ANNEALING OF HIGH PURITY GE AT 340DEGREESK RESULTS IN A CONSIDERABLE REDN. OF HOLE CONCN. DOWN TO 10 PRIME11-CM PRIME3, WHICH IS ASSOCD. WITH A DEEPER LEVEL E SUBV PLUS 0.15 EV APPEARING IN CRYSTALS IRRADIATED AT 180DEGREESK AND ANNEALED AT 300DEGREESK. THE RATE OF DONOR INJECTION HAS 1.6 CM PRIME NEGATIVE1. THE ACTIVATION ENERGIES OF THE ANNEALING AND THE RECOVERY PROCESSES ARE 1.0 AND 1.4 EV, RESP. THE RESULTS ARE INTERPRETED IN TERMS OF SELF ADJUSTING CENTERS CONSISTING OF INTRINSIC DEFECTS: VACANCIES AND INTERSTITIALS. IT IS ASSUMED THAT THE CENTER ASSOCD. WITH THE E SUBV PLUS 0.15 EV LEVEL IS A VACANCY LEVEL, WHICH ALTERS THE SIGN OF ITS CHARGE AT LOWER TEMPS.
NOVOSIBIRSK, USSR.
FACILITY: INST. FIZ. POLUPROV.,

UNCLASSIFIED

172 032
UNCLASSIFIED
TITLE--[INFLUENCE OF THE STRUCTURE OF THE TRANSVERSE MODES OF A RADIATION
SOURCE ON THE HOLOGRAM GENERATED IMAGE -U-
AUTHOR--(02)-STASELKO, D.I., DENISYUK, YU.N.
PROCESSING DATE--04DEC70
COUNTRY OF INFO--USSR
SOURCE--OPTIKA I SPEKTROSKOPIIA, VOL. 28, FEB. 1970, P. 232-330
DATE PUBLISHED---FEB70
SUBJECT AREAS--PHYSICS
TOPIC TAGS--HOLOGRAM, RADIATION SOURCE, PULSE LASER, RUBY LASER
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1992/1483
CIRC ACCESSION NO--AP0112477
STEP NO--UR/0051/70/028/000/0323/0330
UNCLASSIFIED

UNCLASSIFIED

PROCESSING DATE--04DEC70

2/2 032

CIRC ACCESSION NO--AP0112477

ABSTRACT/EXTRACT--(U) GP-0-

ABSTRACT. DERIVATION OF AN EXPRESSION

DESCRIBING THE BRIGHTNESS DISTRIBUTION IN A HOLOGRAM GENERATED IMAGE FOR A LASER EMITTING A SET OF LONGITUDINAL AND TRANSVERSE MODES DURING A LIMITED PERIOD OF TIME. IT IS SHOWN THAT WHEN VIEWING THROUGH SMALL SEGMENTS OF THE HOLOGRAM, THE APPARENT BRIGHTNESS OF THE IMAGE IS MODULATED BY THE SQUARE OF THE TEMPORAL SPATIAL COHERENCE MODULUS OF THE SOURCE. THIS PHENOMENON IS APPLIED TO THE EXPERIMENTAL INVESTIGATION OF THE SPATIAL COHERENCE OF A PULSED RUBY LASER.

UNCLASSIFIED

Acc. No. **AP046227**

Abstracting Service: **S/70**
INTERNAT. AEROSPACE ABST.

Ref. Code:
LLR 0077

A70-23175 # Special features of the behavior of high-resolution emulsions in holography using a pulsed radiation source (Osobennosti povedeniia vysokorazreshalushchikh emul'sii pri golografirovanii s ispol'zovaniem impul'snogo istochnika izlucheniia). D. I. Stasel'ko and A. G. Smirnov, Zhurnal Nauchnoi i Prikladnoi Fotografii-Kinematografii, vol. 15, Jan.-Feb. 1970, p. 66-68, In Russian.

Results of experiments carried out to determine the sensitivity of Soviet Mikrat VR emulsions used to obtain high-quality pulsed holograms. It is found that the Soviet emulsions tested are distinguished by both high sensitivity and small deviations from the reciprocity law. A specially high sensitivity and small deviations from the reciprocity law were noted in the case of laboratory specimens of Mikrat VR emulsion sensitized by dye No. 3912. The sensitivity of these plates during Q-switching was found to exceed the sensitivity of Kodak 649-F plates more than six hundredfold and varied only by a factor of 2 upon switchover to free laser generation, while Kodak 649-F plates varied by a factor of 8 upon switchover to free laser generation. However, industrial specimens of Mikrat VR emulsion were found to be characterized by considerably less sensitivity than laboratory specimens and by large deviations from the reciprocity law. An attempt is made to ascertain the reason for this discrepancy.

A.B.K. /

Als

REEL/FRA
19781343

2/

UDC 536.46+669.715

USSR

BREYTER, A. L., KASHEOROV, L. Ya., MAL'TSEV, V. M., POKHIL, P. F.,
POPOV, Ye. I., PEFDKIN, V. I., and STASENKO, A. G., Moscow

"Burning of Single Particles of Aluminum-Magnesium Alloys in the
Flame of Oxidiser-Fuel Mixture"

Novosibirsk, Fizika Goreniya i Vzryva, Vol 7, No 2, Jun 71,
pp 222-227

Abstract : The burning of single particles of aluminum-magnesium alloys in the tongue of the flame of a mixture of ammonium perchlorate and urotropine of stoichiometric composition (88 % ammonium perchlorate and 12 % urotropine) was experimentally investigated. The investigation results are discussed by reference to photographs of typical tracks of burning particles and diagrams showing the dependences of the inflammation time lag and the particle fraction subjected to explosive burning on particle composition. From the viewpoint of complete burning by modified fuel on aluminum base, alloys with 30-45 % aluminum and 55-70 %

1/2

SR

PREYER, A. L., KASHOROV, L. Ya., et al., Fizika Goreniya i Vzryva, Vol 7,
No 2, Jun 71, pp 222-227

magnesium are considered to be effective. The characteristics of burning of the metal component are determined by the nature of included metals: the permeability of its oxidic layers, reaction capability, surface activity, volatility, fusing temperature, density change by fusing, and the burning temperature. Five illustr., one table, 16 biblio. refs.

2/2

- 39 -

USSR

UDC 620.10

STASENKO, I. V., TKACHEV, V. V.

"Restricted Twisting and Bending of Thinwall Pipe of Nonlinearly Elastic Material"

Izvestiya Vysshikh Uchebnykh Zavedeniy, Mashinostroyeniye, No 1, 1972, pp 5-10.

ABSTRACT: The article states the problem of determination of secondary normal stresses in the zone of a rigid flange with combined bending and twisting of a thinwall tube of a nonlinearly elastic material. The solution produced is based on application of basic assumptions accepted for the calculation of stresses involved in restricted twisting of thinwall shapes.

"APPROVED FOR RELEASE: 09/01/2001

CIA-RDP86-00513R002203130006-4

UNCLASSIFIED
PROCESSING DATE--04DEC70
ACIDS -U- COMPLEXES OF GERMANIUM TETRACHLORIDE WITH O AND M AMINOBENZOIC
AUTHOR--(03)-BELOUSOVA, YE.M., SEYFULLINA, I.I., STASENKO, I.V.
COUNTRY OF INFO--USSR
SOURCE--ZH. OBSHCH. KHIM. 1970, 40(4), 815-17
DATE PUBLISHED-----70

5

SUBJECT AREAS--CHEMISTRY
TOPIC TAGS--GERMANIUM COMPOUND, AMINE, BENZOIC ACID, COMPLEX COMPOUND,
THERMOGRAPHIC ANALYSIS, POTENTIOMETRIC TITRATION, X RAY DIFFRACTION
STUDY

CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--3006/0822
CIRC ACCESSION NO--AP0134555
STEP NO--UR/0079/70/040/004/0815/0817
UNCLASSIFIED

APPROVED FOR RELEASE: 09/01/2001

CIA-RDP86-00513R002203130006-4"

2/2 017
 CIRC ACCESSION NO--AP0134555 UNCLASSIFIED
 ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THERMOGRAPHIC AND CONDUCTIMETRIC
 TITRIMETRY WERE USED TO STUDY THE COMPLEXES FORMED BY D AND M H SUB2 NC
 SUB6 H SUB4 CO SUB2 H WITH GECL SUB4 IN VARIOUS SOLVENTS. THE FOLLOWING
 WERE ISOLATED: GECL SUB4 TIMES 410 H SUB2 NC SUB6 H SUB4 CO SUB2 H)
 TIMES 2ACOH, M. 180DEGREES, WHICH LOST THE ACOH IN SEVERAL MONTHS IN
 OPEN AIR; IN CCL SUB4 THE PRODUCT WAS: GECL SUB4 TIMES 510 H SUB2 NC SUB6
 H SUB4 CO SUB2 H), M. 160DEGREES; GECL SUB4 TIMES 4 1M H SUB2 NC SUB6 H
 SUB4 CO SUB2 H), M. 270DEGREES. X RAY DIFFRACTION DATA WERE TABULATED
 FOR THE COMPLEXES. THE COMPLEX OF THE META ISOMER WAS MORE STABLE
 THERMALLY THAN THAT OF THE ORTHO ISOMER.
 UNIV. IM. MECHNIKOVA, ODESSA, USSR. FACILITY: ODESS. GOS.

UNCLASSIFIED

1/2

025
TITLE--BENDING OF A THIN WALLED TUBE CONSISTING OF LINEARLY HARDENING
MATERIAL -U-
AUTHOR--STASENKO, I.V.
COUNTRY OF INFO--USSR
SOURCE--MOSCOW, IZVESTIYA VYSSHIKH UCHEBNYKH ZAVEDENIY, MASHINOSTROYENIYE,
NO. 1, 1970, PP 8-12
DATE PUBLISHED-----70
UNCLASSIFIED
S
SUBJECT AREAS--MATERIALS, MECH., IND., CIVIL AND MARINE ENGR
TOPIC TAGS--METAL BENDING, PLASTIC DEFORMATION, STRESS DISTRIBUTION, THIN
WALLED METAL TUBE
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRAME--1985/0534
CIRC ACCESSION NO--AT0100988
STEP NO--UR/0145/70/000/001/0008/0012
UNCLASSIFIED

2/2 025

UNCLASSIFIED

PROCESSING DATE--18SEP70

CIRC ACCESSION NO--AT0100988

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THE AUTHOR EXAMINES THE ELASTIC PLASTIC STATE OF A THIN WALLED TUBE UNDER THE COMBINED INFLUENCE OF INTERNAL PRESSURE AND BENDING MOMENT, AND THE PROBLEM OF STRESS DISTRIBUTION IN TUBE CROSS SECTION DURING ELASTIC PLASTIC BENDING IS SOLVED IN TERMS OF THE PLASTIC DEFORMATION THEORY. ALSO CLARIFIED IS THE PROBLEM OF ESTABLISHING A RELATIONSHIP BETWEEN TUBE CURVATURE AND THE MAGNITUDE OF THE INTERNAL FORCES. IT IS DEMONSTRATED THAT, IN THE CASE UNDER CONSIDERATION, AND UNLIKE AN ELASTIC SOLUTION TO THE PROBLEM, PERIPHERAL DEFORMATION OF THE TUBE PROVES TO BE A NONLINEAR FUNCTION OF THE COORDINATE OF A POINT. A FORMULA IS DERIVED FROM WHICH IT IS POSSIBLE TO DETERMINE THE MAXIMUM LOAD ON THE TUBE.

UNCLASSIFIED

USSR

UDC: 541.49-547.583.5:543.257-546.289-547.289

BELOUSOVA, YE.M., SEYFULLINA, I.I., and STASENKO, I.V., Odessa State University
imeni I.I. Mechnikov, Odessa, Ministry of Higher and Secondary Specialized
Education Ukrainian SSR

"Complex Compounds of Germanium Tetrachloride With o- and m-Aminoben-
zoic Acids"

Leningrad, Zhurnal Obshchey Khimii, Vol 40, No 4, Apr 70, pp 815-817

Abstract: The interaction of germanium tetrachloride with o- and m-aminobenzoic acid (OAB and MAB) from solutions in acetic acid and carbon tetrachloride gives compounds of the composition $\text{GeCl}_4 \cdot 4\text{OAB}$.

$2\text{CH}_3\text{COOH}$, $\text{GeCl}_4 \cdot 4\text{MAB}$, $\text{GeCl}_4 \cdot 6\text{OAB}$. The individuality of the compounds was confirmed roentgenographically by comparing the calculated interplanar spacings of the initial and resultant substances. A thermographic study showed that the compound containing six OAB molecules is thermally less stable than the compound with four molecules, but they are more stable than the initial anthranilic acid. The complex compound with MAB is thermally more stable than the compounds with OAB.

7/1

- 34 -

Molecular Physics

-USSR

UDC 539.182+539.184.01

STASIUKAITIS, V. J., KAMINSKAS, V. A., and JUCYS, A. P., Institute of Physics and Mathematics of the Academy of Sciences Lithuanian SSR, Vil'nyus State Pedagogical Institute

"Application of the Extended Method of Calculation and Multiconfigurational Approximation to the Configuration $3d^3$ of Sc I and V III"

Vil'nyus, Litovskiy Fizicheskiy Sbornik, Vol 12, No 6, 1972, pp 903-909

Abstract: Of the refined atomic theory methods, the easiest to use are the multiconfigurational approximation (MCA) and the extended method of calculation (EMC). The present article combines the two methods in the case of the configuration $1s^2 2s^2 2p^6 3s^2 3p^6 3d^3$. Concrete calculations are performed for Sc I and V III. Since the authors are interested mainly in only the 3d-electron shell, the ordinary method of calculation (OMC) is used for all inner shells, and both EMC and MCA are used for the 3d-electron shell. For the inner electrons Hartree-Fock analytic radial orbitals are used for both the ground configuration and the correction configurations. The results obtained in OMC, EMC, MCA, and EMC plus MCA (EMC MCA) are also given for comparison.

1/2

-USSR

STASIUKAITIS, V. J., et al., Litovskiy Fizicheskiy Sbornik, Vol 12, No 6, 1972, pp 903-909

The correction configurations used are $3d^24s$, $3d4p^2$, and $3d4f^2$. In the case of MCA (without EMC) the configuration $3d4d^2$ is also included; it no longer occurs in the case of EMC MCA, since it represents merely the radial correlation which is considered by EMC. Theoretical results are compared with experimental data.

2/2

- 69 -

1/2 017 UNCLASSIFIED PROCESSING DATE--23OCT70
TITLE--KINETICS OF SODIUM DISSOLUTION IN A SODIUM CHLORIDE MELT DURING
DILUTION OF THE METALLIC PHASE WITH LEAD -U-
AUTHOR--(05)-BUSSEMACHUKAS, V.B., KUBASOV, V.L., STATSENKO, S.I., MALANINA,
I.B., ZATELSKIY, S.A.
COUNTRY OF INFO--USSR

SOURCE--ZH. PRIKL. KHIM. (LENINGRAD) 1970, 43(2) 280-4

DATE PUBLISHED-----70

SUBJECT AREAS--CHEMISTRY

TOPIC TAGS--ELECTROLYSIS, SODIUM CHLORIDE, SOLUBILITY, SODIUM, LEAD,
ELECTRIC CURRENT, CHLORIDE

CONTROL MARKING--NO RESTRICTIONS

DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1983/0918

STEP NO--UR/0080/70/043/002/0280/0284

CIRC ACCESSION NO--AP0053842

UNCLASSIFIED

2/2 017

UNCLASSIFIED

PROCESSING DATE--23OCT70

CIRC ACCESSION NO--AP0053842

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THE DISSOLN. RATE OF NA FROM NA-PB LIQ. MIXTS. OF A 1-10 WT. PERCENT NA CONCN. IN AN AGITATED NA₂CL MELT WAS STUDIED EXPTL. IN THE PRESENCE OF CL AT 850DEGREES. THE DEPENDENCE OF THE CURRENT D. OF NA DISSOLN. (I) IN A-CM PRIME2 ON THE NA CONCN. IN THE NA-PB MIXT. IN WT. PERCENT (C) WAS DETD. AS $I \text{ EQUALS } 0.0095C \text{ PRIME2}$. THE CURRENT EFFICIENCY OF THE ELECTROLYSIS OF THE NA₂CL MELT WITH A PB CATHODE IN PERCENT (A) WAS CALCD. AS $A \text{ EQUALS } 100-C.95C \text{ PRIME2-I SUBT}$, WHERE I SUBT IS THE TOTAL CURRENT D. IN A-CM PRIME2. THE CALCNS. AGREE WITH EXPT. PROVING THE FACT THAT CURRENT LOSSES ARE PRIMARILY DETD. BY THE REVERSE DISSOLN. OF NA IN THE NA₂CL MELT AND BY THE REACTION WITH CL.

UNCLASSIFIED

USSR

UDC: 531.74:621.315.431.2

STASEVICH, V. N.

"Effect Which the Alignment of X-Ray Goniometers has on the Accuracy of Measurements of the Angle of a Quartz Crystal Cut"

Elektron. tekhnika. Nauch.-tekhn. sb. Radiokomponenty (Electronic Technology. Scientific and Technical Collection. Radio Components), 1970, vyp. 5, pp 51-68 (from RZh-Radiotekhnika, No 6, Jun 71, Abstract No 6V478)

Translation: The author studies the errors in measurement of the angle of cut of a quartz plate due to flaws in alignment of the x-ray goniometer. It is found that the main causes of error in measurement of the angle of cut are instability of alignment and the use of a narrow slit in front of the counter. It is shown that a shift in angle readings for the specimen is due to the intensity ratio when the x-ray beam is split. Measurement errors due to inaccuracy of goniometer alignment are theoretically calculated, and the computation is experimentally verified. Practical recommendations are given on alignment of x-ray goniometers used in measuring the angles of cut of quartz plates. The results of this work can be used in measurements of the orientation of cuts of any single crystals on x-ray goniometers.

1/1

USSR

UDC: 577.4

ZHUKOVSKIY, Yu. V., STASHEVSKAYA, V. V.

"Construction of a 2^n -Valued Logic Algebra"

Sb. nauch. tr. Khar'kov. in-t mekhaniz. i elektrifik. s. kh. (Collected Scientific Works. Khar'kov Institute of Mechanization and Electrification of Agriculture), 1971, vyp. 20, pp 157-166 (from RZh-Kibernetika, No 4, May 72, Abstract No 5V353)

[No abstract]

USSR

UDC: 51

STASHEVSKAYA, V. V.

"Concerning a Dynamic Programming Problem for a Nonstationary Stochastic Process"

Sb. nauch. tr. Khar'kov. in-t mekhaniz. i elektrifik. s. kh. (Collected Scientific Works. Khar'kov Institute of Mechanization and Electrification of Agriculture), 1971, vyp. 20, pp 35-41 (from RZh-Kibernetika, No 6, Jun 72, Abstract No 6V444)

[No abstract]

1/1

- 28 -

Acc. Nr:

AP0049506

Abstracting Service:
CHEMICAL ABST. 5/70

Ref. Code:

4R0079


100453e Bisformazans and bistetrazolum salts, derivatives of quinaldine quaternary salts. Stashkevich, V. V.; Pilyugin, G. T.; Stashkevich, O. M. (Chernovits. Gos. Univ., Chernovitsy, USSR). *Zh. Obshch. Khim.* 1970, 40(1), 195-202 (Russ). Adding 0.28 g benzidine, 2 ml concd. HCl, and 0.2 g NaNO₂ in H₂O to 1.34 g 2-formyl-1-phenylquinolinium perchlorate phenylhydrazone in pyridine at -10° gave, after 10 hr in the cold, 77.8% I (Ar = Ph, R = R¹ = R² = H), m. 198-9°. Similarly were prepd. the following I (Ar, R, R¹, R², and m.p. given): Ph, H, o-MeO, H, 209-10°; Ph, H, p-MeO, H, 191-2°; p-MeC₆H₄, Me, o-MeO, H, 217-18°; p-MeOC₆H₄, MeO, o-MeO, H, 197-8°; p-BrC₆H₄, Br, o-MeO, H, 212-13°; Me, NO₂, o-MeO, H, 194-5°; Ph, H, H, Me, 205-6°; p-MeC₆H₄, Me, p-MeO, Me, 238-9°; p-MeOC₆H₄, H, o-MeO, Me, 188-90°; Me, NO₂, o-MeO, Me, 171-2°; Ph, H, p-MeO, MeO, 199-200°; p-MeOC₆H₄, MeO, o-MeO, MeO, 215-16°; p-BrC₆H₄, Br, o-MeO, MeO, 205-6°; and Me, NO₂, o-MeO, MeO, — (diiodide m. 215-16°). Treating 0.94 g 2-formyl-1-phenylquinolinium perchlorate phenylhydrazone in pyridine at -10° with the diazonium compd. from 0.24 g p,p'-diaminoazobenzene in aq. HCl-NaNO₂ and holding 2 hr gave 77% II (Ar = Ph, R = R¹ = H), m. 193-4°. Similarly were prepd. the following II (Ar, R, R¹, and m.p. given): p-MeC₆H₄, Me, o-MeO, 199-201°; p-MeOC₆H₄, H, o-MeO, 180-1°; p-BrC₆H₄, Br, o-MeO, 203-4°; and Me, NO₂, o-MeO, 180-1°. Ir, and uv, and electronic spectra data were reported. Heating I in HNO₃ (d. 1.38) to decolorization, gave 35-55% III (Ar,

1/3

REEL/FRA
19801352

7

AP0049506



2/3

19801353

AP0049506

R, R¹, R², and m.p. given): Ph, H, H, H, 206-7°; Ph, H, o-MeO, H, 215-17°; p-BrC₆H₄, Br, o-MeO, H, 219-20°; Me, NO₂, o-MeO, H, 207-8°; Ph, H, H, Me, 207-8°; Me, NO₂, o-MeO, Me, 201-2°; Ph, H, p-MeO, MeO, 213-14°; p-BrC₆H₄, Br, o-MeO, MeO, 224-5°; and Me, NO₂, o-MeO, MeO, 221-2°. Similarly were prepd. the following IV (Ar, R, R¹, and m.p. given): Ph, H, H, 226-7°; p-MeOC₆H₄, H, o-MeO, 219-20°; and Me, NO₂, o-MeO, 204-5°. Uv spectral data for these were reported. The polarographic halfwave potentials of III and IV were tabulated; the 2nd waves had halfwave potentials in the region of -0.43 to -0.63 V. This makes possible the use of these bistetrazolium salts in histochemistry. I possessed internal H bonds, as shown by their ir spectra.

G. M. Kosslapoff

3/3

19801354

NE

Acc. Nr:

AP0049506

Abstracting Service:
CHEMICAL ABST. 5/70

Ref. Code:

UR0079

100453e Bisformazans and bistetrazolium salts, derivatives of quinaldine quaternary salts. Stashkevich, V. V.; Pilyugin, G. T.; Stashkevich, O. M. (Chernovitsk Gos. Univ. Chernovitsy, USSR). *Zh. Obshch. Khim.* 1970, 40(1), 195-202 (Russ). Adding 0.28 g benzidine, 2 ml concd. HCl, and 0.2 g NaNO₂ in H₂O to 1.34 g 2-formyl-1-phenylquinolinium perchlorate phenylhydrazone in pyridine at -10° gave, after 10 hr in the cold, 77.8% I (Ar = Ph, R = R¹ = R² = H), m. 198-9°. Similarly were prepd. the following I (Ar, R, R¹, R², and m.p. given): Ph, H, o-MeO, H, 209-10°; Ph, H, p-MeO, H, 191-2°; p-MeC₆H₄, Me, o-MeO, H, 217-18°; p-MeOC₆H₄, MeO, o-MeO, H, 197-8°; p-BrC₆H₄, Br, o-MeO, H, 212-13°; Me, NO₂, o-MeO, H, 194-5°; Ph, H, H, Me, 205-6°; p-MeC₆H₄, Me, p-MeO, Me, 238-9°; p-MeOC₆H₄, H, o-MeO, Me, 188-90°; Me, NO₂, o-MeO, Me, 171-2°; Ph, H, p-MeO, MeO, 199-200°; p-MeOC₆H₄, MeO, o-MeO, MeO, 215-16°; p-BrC₆H₄, Br, o-MeO, MeO, 205-6°; and Me, NO₂, o-MeO, MeO, — (diiodide m. 215-16°). Treating 0.94 g 2-formyl-1-phenylquinolinium perchlorate phenylhydrazone in pyridine at -10° with the diazonium compd. from 0.24 g p,p'-diaminoazobenzene in aq. HCl-NaNO₂ and holding 2 hr gave 77% II (Ar = Ph, R = R¹ = H), m. 193-4°. Similarly were prepd. the following II (Ar, R, R¹, and m.p. given): p-MeC₆H₄, Me, o-MeO, 199-201°; p-MeOC₆H₄, H, o-MeO, 180-1°; p-BrC₆H₄, Br, o-MeO, 203-4°; and Me, NO₂, o-MeO, 180-1°. Ir, and uv, and electronic spectra data were reported. Heating I in HNO₃ (d. 1.38) to decolorization, gave 35-45% III (Ar,

1/3

REEL/FRA
19801352

7

AP0049506

R, R¹, R², and m.p. given): Ph, H, H, H, 206-7°; Ph, H, o-MeO, H, 215-17°; p-BrC₆H₄, Br, o-MeO, H, 219-20°; Me, NO₂, o-MeO, H, 207-9°; Ph, H, H, Me, 207-8°; Me, NO₂, o-MeO, Me, 201-2°; Ph, H, p-MeO, MeO, 213-14°; p-BrC₆H₄, Br, o-MeO, MeO, 224-5°; and Me, NO₂, o-MeO, MeO, 221-2°. Similarly were prep'd. the following IV (Ar, R, R¹, and m.p. given): Ph, H, H, 226-7°; p-MeOC₆H₄, H, o-MeO, 219-20°; and Me, NO₂, o-MeO, 204-5°. Uv spectral data for these were reported. The polarographic halfwave potentiels of III and IV were tabulated; the 2nd waves had halfwave potentiels in the region of -0.43 to -0.63 V. This makes possible the use of these bistetrazolium salts in histochemistry. I possessed internal H bonds, as shown by their ir spectra.

G. M. Kosolapoff

3/3

19801354

nk

1/2 037 UNCLASSIFIED PROCESSING DATE--30OCT70
TITLE--SYNTHESIS AND OPTIMAL FILTRATION OF WIDEBAND SIGNALS BY DISPERSIVE
ULTRASONIC DELAY LINES AND THE POTENTIAL NOISE STABILITY OF ANALOG DATA
AUTHOR--STASHUK, L.D.
COUNTRY OF INFO--USSR
SOURCE--RADIOELEKTRONIKA, VOL. 8, MAR. 1970, P. 299-308, IZY, VUZ
DATE PUBLISHED--MAR70
SUBJECT AREAS--ELECTRONICS AND ELECTRICAL ENGR., PHYSICS
TOPIC TAGS--PULSE SIGNAL, SIGNAL PROCESSING, ELECTRIC FILTER, FILTRATION,
ACOUSTIC DELAY LINE, PULSE MODULATION
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRAE--2000/0544 STEP NO--UR/0452/70/008/000/0299/0308
CIRC ACCESSION NO--AP0124239
UNCLASSIFIED

2/2 037

UNCLASSIFIED

PROCESSING DATE--30OCT70

CIRC ACCESSION NO--AP0124239

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. INVESTIGATION OF GENERAL PROBLEMS CONCERNING THE SYNTHESIS AND OPTIMAL FILTRATION OF WIDEBAND PULSE SIGNALS WITH LINEAR FREQUENCY MODULATION. THE FILTRATION IS ACCOMPLISHED BY A DISPERSIVE ULTRASONIC DELAY LINE TREATED AS A FOUR TERMINAL NETWORK WITH A FREQUENCY DEPENDENT DELAY CHARACTERISTIC. EXPRESSIONS ARE DERIVED FOR EXPANDED AND COMPRESSED SIGNALS AT DIFFERENT WAVEFORMS AND INITIAL PULSE SHAPES. ATTENTION IS GIVEN TO THE POSSIBILITY OF ANALOG TRANSFER OF INFORMATION USING THE WIDEBAND SIGNALS AS CARRIERS; THE POTENTIAL (IN THE SENSE OF KOTELNIKOV) NOISE STABILITY OF CERTAIN MODULATION TYPES IS ESTIMATED.

UNCLASSIFIED

USSR

UDC: 621.396:621.374.5

~~STASHUK, L. D.~~

"Synthesis and Optimal Filtration of Broad-Band Signals by Dispersion Ultrasonic Delay Lines and the Potential Noise Immunity of Analogous Information Transmission in the Use of Such Signals"

Kiev, Izvestiya Vuzov SSSR--Radioelektronika, Vol. 13, No. 3, 1970, pp 299-308

Abstract: In the synthesis of a broad-band linear frequency modulation signal, the ultrasonic dispersion delay line performs the function of a conjugate filter excited at its input by an ordinary pulse. The synthesis process is analyzed with the delay line excited by pulses with various types of envelope: square, triangular, $(\sin x)/x$, and bell-shaped. A table is given of the results of this analysis; it gives the spectral function corresponding to the different signal types, the expanded linear frequency modulated signal, the spectral function of the expanded linear frequency modulated signal, and the compressed signal expressions.

1/2

USSR

STASHUK, L. D., Izvestiya Vuzov SSSR--Radioelektronika, Vol. 13,
No. 3, 1970, pp 299-308

Oscillograms of the broad-band expanded and compressed linear FM
signal at the optimal filter output are shown.

2/2

- 52 -

Acc. Nr:

AP0038107

S

Ref. Code: UR 0326

PRIMARY SOURCE: Fiziologiya Rasteniy, 1970, Vol 17, Nr 1,
pp 71-75

DEPENDENCE OF CONTENT OF GIBBERELLIN-LIKE SUBSTANCES
IN SUMMER WHEAT LEAVES ON CONDITIONS
OF PLANT NUTRITION AND LEAF AGE

Stasilyunas, O. A.

N. I. Vavilov All-Union Institute of Plant Growing, Leningrad

Summer wheat was grown in field and vegetation conditions with sufficient (addition of NPK in the tillering and shooting phases) or insufficient nutrition (without additional nutrients). Gibberellin-like substances were extracted from 5 and 10 day old leaves of the last tier and also from leaves of the preceding tier by means of paper chromatography. The growth activity of the substances was determined by a biotest (pea shoots). In all leaf samples the amount of gibberellin-like substances was higher in the case of added nutrients than in the case of insufficient nutrition of the plants. Irrespective of level of nutrition there were more gibberellin-like substances in the last leaves when they were 5 days old than when they were 10 days old. Two zones of gibberellin-like activity with R_f 0.10-0.30 and 0.50-0.70 were found. The latter corresponds to GA. The content of gibberellin-like substances did not correlate with the leaf area.

REEL/FRAME

19731157

02

003

1/2 007 UNCLASSIFIED PROCESSING DATE--23OCT70
TITLE--INTERLEVEL DIFFERENCES IN IRON GROUP ATOMIC SYSTEMS IN THE EXTENDED
METHOD OF CALCULATION -U-
AUTHOR--(02)-JUCYS, A., STASIUKAITIS, V. STASYUKAYTIS
YUTSIS, A.P. STASYUKAYTIS, V.
COUNTRY OF INFO--USSR
SOURCE--INT. J. QUANTUM CHEM. 1970, 4(3), 333-5
DATE PUBLISHED-----70
SUBJECT AREAS--CHEMISTRY
TOPIC TAGS--IRON, ATOMIC PROPERTY
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRAME--1998/0441 STEP NO--US/0000/70/004/003/0333/0035
CIRC ACCESSION NO--AP0121115
UNCLASSIFIED

2/2 007

UNCLASSIFIED

PROCESSING DATE--23OCT70

CIRC ACCESSION NO--AP0121115

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THE EXTENDED METHOD OF CALC. HAS BEEN APPLIED TO CALC. THE INTER LEVEL DIFFERENCES OF THE SHELL OF 3D ELECTRONS IN THE FE GROUP AT. SYSTEMS. THE H LIKE RADIAL ORBITALS HAVE BEEN USED. THE RESULTS ARE COMPARED WITH THOSE OBTAINED BY ORDINARY METHODS OF CALC. AS WELL AS WITH EXPTL. DATA. FACILITY: DEP. THEOR. PHYS., V. KAPSUKAS STATE UNIV., VILNIUS, USSR.

UNCLASSIFIED

USSR

STASYUNAS, A. S., KEMESHIS, P. P.

UDC 621.372.061

"Properties of Parametric Filters with Switching Multipliers"

Techn. kibernetika, Tekhn. kibernetika (Technical Cybernetics), Kaunas, 1970, pp 282-290 (from RZh-Radiotekhnika, No 8, Aug 70, Abstract No 8A139)

Translation: This article contains an investigation of the properties of non-inductive parametric filters simultaneously realizing filtration and transposition of signals where periodic (square) multiplier signals are used instead of harmonic reference multiplier signals.

1/1

USSR

UDC 621.391:519.2

STASYUNAS, A. S., KEMESHIS, P. P.

"Synthesis of Parametric Filters Simultaneously Realizing Signal Filtration and Transposition"

Techn. kibernetika, tekhn. kibernetika (Technical Cybernetics), Kaunas, 1970, pp 275-281 (from RZh-Radiotekhnika, No 8, Aug 70, Abstract No 8A109)

Translation: In this article the problem of synthesizing noninductive parametric filters simultaneously realizing signal filtration and transposition to any frequency range is solved.

1/1

USSR

UDC: 621.372.54.061

ZAYEZDNYI, A. M., KEMESHIS, P. P., and STASYUKAS, A. S.

"Theoretical Bases of the Design of Parametric Filters Equivalent to Linear Filters"

Kiev, Izvestiya VUZ USSR--Radioelektronika, No 10, 1972, pp 1195-1203

Abstract: The parametric filters under discussion in this article are RC circuits designed to replace filters using inductances. As defined here, the parametric filter is a circuit consisting of resistors and a single capacitor, with one of the resistors varying in accordance with the control circuit signal. The linear filter consists of elements with constant parameters and can be described by the n-th order linear differential equation

$$\sum_{i=0}^n a_i \frac{d^i}{dt^i} x(t) = f(t)$$

with constant coefficients. The problem the authors set themselves is stated in this way: Given the differential equation or transfer
1/2

USSR

ZAYEZDNYI, A. M., et al, Izvestiya VUZ USSR--Radioelektronika,
No 10, 1972, pp 1195-1203

function of a physically realizable circuit, and given an external action $f(t)$ and the circuit reaction $x(t)$; required, to synthesize the circuit realizing the transformation of $f(t)$ into $x(t)$ under the condition that the circuit contain parametric filters and summer circuits of the same type connected in parallel. Three possible methods of solving the problem are offered: use of the Lagrange method of variation of constants, transition to the transfer function, and the recurrent method of finding periodic solutions.

2/2

- 17 -

USSR

UDC 539.5

DOTSENKO, V. I., PUSTOVALOV, V. V., STATINOVA, V. F., Kar'kov.

"Deformation Hardening of Copper at Low Temperatures"

Kiev, Problemy Prochnosti, No. 4, Apr 71, p. 41-46.

Abstract: The temperature dependences of the parameters of the hardening curves of copper monocrystals of various orientation and copper polycrystals of various purity are studied. It is demonstrated that as the temperature drops from 4.2 to 1.4°K, the critical shear stress of copper monocrystals of all three main orientations decreases. Two types of unevenness of the hardening curve of monocrystals are studied, observed at low temperatures. The stress relaxation method is used to produce values of the activation energy and activation volume of the process controlling plastic deformation.

1/1

- 87 -

Optimization

USSR

UDC 518.1

1

ARTOBOLVSKIY, I. I., Academician, GENKIN, M. D., GRINKEVICH, V. K., SOBOLOV, I. M., and STATNIKOV, R. B., State Scientific Research Institute of Mechanical Engineering, Moscow

"Optimization in Machine Theory by LP-Search"

Moscow, Doklady Akademii Nauk SSSR, Vol 200, No 6, 1971, pp 1287-1290

Abstract: The principal types of optimization problems occurring in machine theory are optimal analysis problems, optimal synthesis problems, and best approximation problems. They are all multiparametric and the use of classical methods of the calculus of variations is, as a rule, impossible. A global search is necessary. An "independent" random search (Monte Carlo method) permits the simultaneous optimization of all criteria that are of interest. The selection of the decision or compromise criterion can be made during the "man-machine" dialogue. Further improvement of the model (if it is required) is possible by using local search methods, which usually converge in the neighborhood of the extremum. The authors suggest that, instead of a random search, its deterministic analog -- an LP-search -- be used. It has led to much

1/2

JR

ARTOBOLVSKIY, I. I., et al., Doklady Akademii Nauk SSSR, Vol 200, No 6, 1971, pp 1287-1290

better results than the random search in a number of complex problems, with the number of samples reduced 2-4 times. The article describes the scheme for the LP-search and considers the example of an oscillatory system with three degrees of freedom, in which it is necessary to find the model with the minimum length and the model with the maximum difference between the first and second natural frequencies subject to restrictions.

2/2

- 137

STATNIKOV, R. B.

SPAS 54729
17 Dec 71

UDC 518.1
METHOD
OPTIMIZATION IN THE THEORY OF MACHINES, USING THE IP-SEARCH

Article by Academician I. I. Arkobolevskiy, M. D. Genkin,
V. E. Gindovitch, I. N. Sobol, and R. B. Statnikov, State
Scientific Research Institute of Machine Control, State
Postally Akademii Nauk SSSR, Vol 200, No 6, 1971, pp 1267-1290

The problems of optimum planning are particularly pressing under series production conditions and in the designing of expensive experiments.

Optimum planning includes both a search for a design plan (and its corresponding parameters) according to the given plan by criteria and the creation of new mathematical methods that consider the specifics of complex multiparametric and multi-criteria problems.

I. Instead of the concepts machine, mechanism, design and so forth, we will introduce a nondimensional analysis model. For a given kinematic structure and n degrees of freedom, the model is determined by the point $\alpha = (\alpha_1, \dots, \alpha_n)$ of the n -dimensional parallelepiped G in n -space.

where $\alpha_i \in [\alpha_i^{\min}, \alpha_i^{\max}]$, $1 \leq i \leq n$. (1)
The model's parameters are the limits of the permissible variations of the system's behavior isolates some closed section G' in parallelepiped (1); we consider G' volume to be positive.

If the quality of the model is determined by a function $\phi(\alpha)$ (the quality criterion), which is defined in G , then we call that model α' , such that $\phi(\alpha') = \sup_{\alpha \in G} \phi(\alpha)$, an optimum model.

Let us agree to write $\phi(G)$, if $\phi(\alpha)$ is defined in G .

Let us examine the basic types of optimization problems that arise in the theory of machines.

Machine Control

USSR

UDC 621.774.35.001.4

2

PLYATSKOVSKIY, O. A., Doctor of Technical Sciences, POROKHNIKOV, YU. Z.,
SULADZE, O. N., STATNIKOV, V. M., UBIRIYA, A. YE., Candidate of Technical
Sciences, and TSERETELI, P. A.
Principal Parameters of the Deformation Process by High-Temperature Thermo-
mechanical Treatment of Pipes"

Dnepropetrovsk Metallurgicheskaya i Gornorudnaya Promyshlennost', No 4,
(70), Jul-Aug 71, pp 34-37

Abstract: At many active pipe rolling plants, reduction mills can be utilized for high-temperature thermomechanical treatment (HTMT) of pipes. Workers of the All-Union Scientific Research Institute of Pipes and specialists of the Rustavsk Metallurgical Plant have developed the technology of HTMT of hot-rolled compressor pump pipes (73 x 5.5 mm) of carbon steels (brands 20 and 35) and low-alloyed steel (36G2S) by rolling on a 20-cage reduction mill with rolls 350-400 mm in diameter. The HTMT technology is discussed by reference to diagrams showing the general arrangement and the change of the metal pressure on rolls under different rolling conditions. In HTMT the metal pressure on the rolls of pipes with precooling in deforming cases is approximately twice as high as in the standard process of hot reduction. Investigation data were used for planning an industrial experimental produc-
1/2

USSR

PLYATSKOVSKIY, O. A., et al., Metallurgicheskaya i Gornorudnaya Promyshlennost', No 4 (70), Jul-Aug 71, pp 34-37

tion sector of high-quality compressor pump pipes. Two illustrations, one table, three bibliographic references.

2/2

- 72 -

USSR


UDC 546.289+546.23

KARBANOV, S. G., STATNOVA, YE. A., ZLOMANOV, V. P., and NOVOSELOVA, A. V.,
Chair of Inorganic Chemistry

"Study of the System Germanium-Selenium in the Proximity of Germanium Monoselenide and the Growth of Its Monocrystals"

Moscow, Vestnik Moskovskogo Universiteta, Vol 13, No 5, Sep-Oct 72, pp 531-534

Abstract: The system Ge-Se has been studied by directed crystallization in the composition range 49.99-51.00% Se. Germanium monoselenide has been found to melt incongruently:



Monocrystals of germanium selenide were grown by the sublimation method in a closed system with movement of the ampule and under static conditions. Following parameters were obtained for the elementary nucleus by x-ray analysis: $a = 4.42 \pm 0.02$, $b = 3.87 \pm 0.02$, and $c = 10.85 \pm 0.05$ Å.

1/1

- 23 -

172 032
UNCLASSIFIED
TITLE--THERMODYNAMIC PROPERTIES OF MOLTEN ALLOYS OF THE
LEAD, SODIUM, BISMUTH SYSTEM -U-
AUTHOR--(03)--MORACHEVSKY, A.G., STASENKO, S.I., BUSSEMACHUKAS, V.B.
PROCESSING DATE--04DEC70
COUNTRY OF INFO--USSR
SOURCE--IZVEST. V.U.Z. TSVETNAYA MET., 1970, (2), 97-101
DATE PUBLISHED-----70
SUBJECT AREAS--MATERIALS
TOPIC TAGS--THERMODYNAMIC PROPERTY, ORDERED ALLOY, ELECTROMOTIVE FORCE,
LEAD ALLOY, SODIUM ALLOY, BISMUTH ALLOY, SODIUM CHLORIDE, CALCIUM
CHLORIDE, BARIUM CHLORIDE, ENTROPY, GLASS
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--3003/1498
STEP NO--UR/0149/70/000/002/0097/0101
CIRC ACCESSION NO--AT0130427
UNCLASSIFIED

2/2 032

UNCLASSIFIED

PROCESSING DATE--04DEC70

CIRC ACCESSION NO--AT0130427

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. THE THERMODYNAMIC PROPERTIES OF A NUMBER OF ALLOYS OF THE PB,NA,BI SYSTEM WERE STUDIED BY MEASURING THE E.M.F OF (MINUS)NA, GLASS, (NACL-CACL SUB2 -BACL SUB2) SUBEUT, GLASS, PB(N SUBPB), NA (N SUBNA), BI(N SUBBI) (PLUS) CONCENTRATION CELLS BETWEEN THE TEMP. OF THE LIQUIDUS LINE AND 910DEGREESC. THE NEGATIVE VALUES OF THE ENTROPY OF MIXING OBTAINED FOR THE SYSTEM WERE ATTRIBUTED TO THE EXISTENCE OF ORDERING IN THE ALLOYS, SIMILAR TO THAT CHARACTERIZING SUCH COMPOUNDS AS NA SUB3 BI..

UNCLASSIFIED

1/2 037
UNCLASSIFIED
PROCESSING DATE--20NOV70
TITLE--ACCEPTOR ROLE OF MOLYBDENUM IN AN ALLOY WITH NICKEL -U-
AUTHOR--(04)-KALINOVICH, D.F., KOVENSKIY, I.I., SMOLIN, M.D., STATSENKO,
V.M.
COUNTRY OF INFO--USSR
SOURCE--FIZ. METAL METALLOVED. 1970, 29(3), 653-5
DATE PUBLISHED-----70
SUBJECT AREAS--MATERIALS, PHYSICS
TOPIC TAGS--MOLYBDENUM CONTAINING ALLOY, NICKEL ALLOY, IONIZATION,
ELECTRON ACCEPTOR, ELECTRON DONOR, NICKEL ISOTOPE, MOLYBDENUM ISOTOPE
CTRL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRAME--3001/0341
STEP NO--UR/0126/70/029/003/0653/0655
CIRC ACCESSION NO--AP0126097
UNCLASSIFIED

2/2 037

UNCLASSIFIED

PROCESSING DATE--20NOV70

CIRC ACCESSION NO--APO126097

ABSTRACT/EXTRACT--(U) GP-0- ABSTRACT. BY USING RADIOACTIVE PRIME63 NI AND PRIME99 MO AND THE METHOD OF ELECTRON TRANSFER, THE SIGN AND IONIZATION DEGREE OF MO ATOMS IN THE ALLOY NI,MO 20 AT. PERCENT AT 950-1300DEGREES WERE DETD. EQUATIONS WERE OBTAINED FROM THE TEMP. DEPENDENCE OF MO AND NI DIFFUSION COEFFS. THE FOLLOWING VALUES WERE DETD. FOR THE EFFECTIVE CHARGE OF THE MIGRATING IONS, TAKING INTO CONSIDERATION ALL FORCES WHICH MAY ACT ON THE IONS DURING ELECTRON TRANSFER FOR NI AND MO (1ST AND 2ND FIGURES, RESP.): AT 950DEGREES 38.8, NEGATIVE 9.90 ESU, 2.95 TIMES 10 PRIME NEGATIVE10, 4.05 TIMES 10 PRIME NEGATIVE10 CM PRIME2-SEC; AT 1050DEGREES 37.5, NEGATIVE 9.45 ESU, 1.29 TIMES 10 PRIME NEGATIVE9, 1.86 TIMES 10 PRIME NEGATIVE9 CM PRIME2-SEC; AT 1150DEGREES 36.3, NEGATIVE 8.96 ESU, 5.30 TIMES 10 PRIME NEGATIVE9, 6.83 TIMES 10 PRIME NEGATIVE9 CM PRIME2-SEC; AT 1300DEGREES 33.5, NEGATIVE 8.23 ESU, 2.86 TIMES 10 PRIME NEGATIVE8, 3.47 TIMES 10 PRIME NEGATIVE8 CM PRIME2-SEC. THE VALUES OF THE EFFECTIVE CHARGE FOR NI AND MO INDICATE A DONOR ACCEPTOR INTERACTION. FACILITY: INST. PROBL. MATERIALVED., KIEV, USSR.

UNCLASSIFIED

USSR

UDC: 519.24

STATULYAVICHUS, V.

"On Limit Theorems for Random Functions. 1"

Lit. mat. sb. (Lithuanian Mathematics Collection), 1970, 10, No 3, pp 583-592 (from RZh-Kibernetika, No 7, Jul 71, Abstract No 7V63)

Translation: An investigation is made into the asymptotic behavior of probabilities $1 - F_{Z(0,T)}(x)$, $F_{Z(0,T)}(-x)$ of large deviations, and the rate of convergence of the functions $F_{Z(0,T)}(x)$ to $\Phi(x)$ for the random quantity

$Z(0,T) = \frac{\zeta(0,T) - M\zeta(0,T)}{\sqrt{D\zeta(0,T)}}$ as $T \rightarrow \infty$, where $\zeta(s,t)$ is a function which is

additively dependent on the interval $[s,t]$ such that its corresponding σ -algebras $\mathcal{F}_{s,t} = \sigma\{\zeta(u,v), (u,v) \subset [s,t]\}$ satisfy conditions of weak dependence of "near-Markovian" type (the RM condition):

$$\sup_{C \in \mathcal{F}_{s,t}} |P(C|A) - P(C|B)| \leq e^{-\alpha_T(t-s)}$$

1/2

STATULYAVICHUS, V., Lit. mat. sb., 1970, 10, No 3, pp 583-592

for all $A \in \mathcal{F}_s, B \in \mathcal{F}_t, 0 \leq s < t < T$, where the coefficient of regularity $\alpha_T > 0$.
An investigation is also made of semi-invariant conditions for mixed
semi-invariants $\Gamma_k(\xi(t_1), \dots, \xi(t_k))$ of the process $\xi(t)$ for the investigation

of $\xi(s, t) = \int_s^t \xi(t) dt$. An estimate is obtained for $\Gamma_k(\xi(t_1), \dots, \xi(t_k))$, when $\xi(t)$
satisfies a regularity condition of type RM, or behavior of the mixed
moments

$$M \xi(t_1) \xi(t_2) \dots \xi(t_k),$$

is known, where the sign $\sim$ indicates that the random quantities are
centered:

$$\tilde{\xi} = \xi - M\xi.$$

Author's abstract.

172 045
UNCLASSIFIED
TITLE--CALORIMETRIC FLOW METER FOR CORROSIVE LIQUIDS --U--
PROCESSING DATE--16OCT70
AUTHOR--STATVUKHA, G.A.
COUNTRY OF INFO--USSR
SOURCE--KHIM. PROM. UKR. 1970, (1), 44-5
DATE PUBLISHED-----70
SUBJECT AREAS--MECH., IND., CIVIL AND MARINE ENGR, METHODS AND EQUIPMENT
TOPIC TAGS--CORROSION, METAL TUBE, STRUCTURAL PLASTIC, FLUID FLOW, FLOW
METER
CONTROL MARKING--NO RESTRICTIONS
DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1996/1667
STEP NO--UR/0436/70/000/001/0044/0045
CIRC ACCESSION NO--AP0118645
UNCLASSIFIED

2/2

045

CIRC ACCESSION NO--AP0118645
ABSTRACT/EXTRACT--(U) GP-0-

UNCLASSIFIED

PROCESSING DATE--16OCT70

ABSTRACT. THE DIAGRAM AND PARAMETERS ARE GIVEN OF A CALORIMETRIC FLOW METER WITH FLUOROPLAST TUBE INSTEAD OF A METAL ONE. STATIC AND DYNAMIC CHARACTERISTICS OF THE METER ARE DISCUSSED. THE TIME CONST. OF THE FLUOROPLAST TUBE IS TWICE THAT OF THE METAL TUBE OF IDENTICAL DIMENSIONS. THE PROPOSED METER MAKES IT POSSIBLE TO MEASURE FLOWS SMALLER THAN OR EQUAL TO 200 L.-HR. THE ERROR OF THE MEASUREMENT IS SMALLER THAN OR EQUAL TO 2PERCENT.

UNCLASSIFIED

USSR

UDC 547.62.24

DOKUNIKHIN, N. S., SOLODAR', S. L., and STAVINCHUK, V. G., Scientific Research Institute of Organic Intermediate Products and Dyes, Moscow

"Conversions of Polycyclic Ketones. The Action of Phosphorus Oxychloride on Phenalenone and 1,3(2H)-Phenalendione"

Leningrad, Zhurnal Organicheskoy Khimii, Vol 9, No 2, Feb 73, pp 375-377

Abstract: On heating with phosphorus oxychloride phenalenone and 1,3(2H)-phenalendione form 1-chloroperopyrene, m.p. 327-329°, and 1,3,7-trichloroperopyrene, m.p. 336-337°, respectively which can then be reduced to peropyrene. Oxidation of 1-chloroperopyrene with dilute nitric acid gave perylene-3,4,9,10-tetracarboxylic acid. The structure of 1,3,7-trichloroperopyrene was established by oxidizing it to 2-chloroperylene-3,4,9,10-tetracarboxylic acid, followed by conversion to the known 2-hydroxy-perylene-3,4,9,10-tetracarboxylic acid.

1/1

- 36 -

USSR

UDC 612.111.31.014.426

KHOLODNYI, A. Ya., STAVINSKAYA, L. I., and CHESNOKOV, F. T., Blood and Tissue
Center, Military Medical Academy imeni S. M. Kirov, Leningrad

"Change in Viability of Erythrocytes Irradiated With Microwaves"

Moscow, Problemy Gematologii i Perelivaniya Krovi, Vol 15, No 7, Jul 70, pp 39-41

Abstract: A study was made of the effect of microwaves on peripheral blood erythrocytes under conditions of extracorporeal circulation. The acid stability of erythrocytes in the blood of irradiated dogs, was determined prior to and after irradiation. The time of stay of Cr⁵¹ labeled erythrocytes in the vessels was also studied. It was found that irradiation ($\lambda = 12.5$ cm) of the dogs decreased the lifetime of erythrocytes, as evidenced by a reduction in acid stability and a decrease in time of stay in the vessels.

1/1

1/2 026

UNCLASSIFIED

PROCESSING DATE--09OCT70

TITLE--ON BIOLOGICAL ADEQUACY OF BLOOD USED FOR REINFUSION -U-

AUTHOR--(02)--ZHURAVLEV, YU.N., STAVINSKAYA, L.I.

COUNTRY OF INFO--USSR

SOURCE--VESTNIK KHIRURGII IMENI I. I. GREKOVA, 1970, VOL 104, NR 5, PP
110-113

DATE PUBLISHED-----70

SUBJECT AREAS--BIOLOGICAL AND MEDICAL SCIENCES

TOPIC TAGS--STORED BLOOD, BLOOD TRANSFUSION, ERYTHROCYTE

CONTROL MARKING--NO RESTRICTIONS

DOCUMENT CLASS--UNCLASSIFIED
PROXY REEL/FRA--1990/0578

STEP NO--UR/0589/70/104/005/0110/0113

CIRC ACCESSION NO--AP0108793

UNCLASSIFIED

2/2 026

UNCLASSIFIED

PROCESSING DATE--09OCT70

CIRC ACCESSION NO--AP0108793

ABSTRACT/EXTRACT--(U) GP-0-

ABSTRACT. USING A RADIOACTIVE METHOD THE
AUTHORS HAVE STUDIED THE POSTTRANSFUSION INTAKE AND DURATION OF
SEMIPERIOD OF ERYTHROCYTES LIFE IN AUTOBLOOD TAKEN FROM THE OPERATIVE
WOUND AND WASHED ERYTHROCYTES IN DRAINAGE BLOOD. THE CONCLUSION IS
DRAWN ON HIGH BIOLOGICAL ADEQUACY OF BLOOD TAKEN FROM THE OPERATIVE
WOUND AND WASHED ERYTHROCYTES OF DRAINAGE BLOOD IN ITS PROMPT ENTERING A
RESERVOIR. STORAGE OF THE COLLECTED DRAINAGE BLOOD IN A REFRIGERATOR
DOES NOT EFFECT THE DURATION OF ERYTHROCYTES LIFE. FACILITY:
KHIRURGICHESKOY KLINIKI USOVERSHENSTVOVANIYA VRACHEY IM. P. A.
KUPRIYANOVA AND N I LABORATORII, TSENTRA KROVI I TKANEY VOYENNO
MEDITSINSKOY ORDENA LENINA KRASNOZNAMENNOY AKADEMII IM. S. M. KIROVA.

UNCLASSIFIED

USSR

UDC:621.313.12:539.172.12

S 6
BOL'SHOV, V. I., DUBININ, A. A., DMITRIYEV, V. M., KAPCHIGASHEV,
S. P., KON'SHIN, V. A., MATUSEVICH, YE. S., POLIVANSKIY, V. P.,
PUPKO, V. Ya., REGUSHEVSKIY, V. I., STAVISSKIY, Yu. Ya., and
YUR'YEV, Yu. S.

"Physical Investigation of the Target in an Electronuclear
Neutron Flux Generator"

Moscow, Atomnaya Energiya, Vol 28, No 5, May 70, pp 388-392

Abstract: Fluxes of thermal neutrons on the order of 10^{17} - 10^{18}
 $n/cm^2 \cdot sec$ open new possibilities for investigations in many
areas of science and technology. There is great interest in
the study of the possibility for increasing neutron fluxes by
using the process of multiple neutron birth upon interaction
of nucleons with energies in the hundreds of MeV with heavy
nuclei. This article presents the results of experiments and
calculations concerning the neutron-physical characteristics

1/2

USSR

BOL'SHOV, V. I., DUBININ, A. A., DMITRIYEV, V. M., KAPCHIGASHEV, S. P., KON'SHIN, V. A., MATUSEVICH, Y. E. S., TOLIVANSKIY, V. P., TUPKO, V. Ya., REGUSHEVSKIY, V. I., STAVISSKIY, Yu. Ya., YUR'YEV, Yu. S., Moscow, Atomnaya Energiya, Vol 28, No 5, May 70, pp 388-392

of the target in an electronuclear device for the generation of neutron fluxes. The yield of neutrons and distribution of the number of reactions in a heavy target and moderator are measured. The space-energy distribution of neutron flux in the moderator is calculated and the accumulation of transuranium elements in a system with high neutron flux is computed.

2/2

USSR

UDC:621.313.12:539.172.12

BOL'SHOV, V. I., DUBININ, A. A., DMITRIYEV, V. M., KAPCHIGASHEV, S. P., KON'SHIN, V. A., MATUSEVICH, YE. S., POLIVANSKIY, V. I., TUPKO, V. Ya., REGUSHEVSKIY, V. I., STAVISSKIY, Yu. Ya., and YUR'YEV, Yu. S.

"Physical Investigation of the Target in an Electronuclear Neutron Flux Generator"

Moscow, Atomnaya Energiya, Vol 28, No 5, May 70, pp 388-392

Abstract: Fluxes of thermal neutrons on the order of 10^{17} - 10^{18} n/cm².sec open new possibilities for investigations in many areas of science and technology. There is great interest in the study of the possibility for increasing neutron fluxes by using the process of multiple neutron birth upon interaction of nucleons with energies in the hundreds of MeV with heavy nuclei. This article presents the results of experiments and calculations concerning the neutron-physical characteristics

1/2

USSR

BOL'SHOV, V. I., DUBININ, A. A., DMITRIYEV, V. M., KAPCHIGASHEV, S. P., KON'SHIN, V. A., MATUSEVICH, Y. E. S., TOLIVANSKIY, V. P., TUPKO, V. Ya., REGUSHEVSKIY, V. I., STAVISSKIY, Yu. Ya., YUR'YEV, Yu. S., Moscow, Atomnaya Energiya, Vol 28, No 5, May 70, pp 388-392

of the target in an electronuclear device for the generation of neutron fluxes. The yield of neutrons and distribution of the number of reactions in a heavy target and moderator are measured. The space-energy distribution of neutron flux in the moderator is calculated and the accumulation of transuranium elements in a system with high neutron flux is computed.

2/2

USSR

UDC 621.372.837(088.8)

KOZLOV, V. I., STAVITSKAYA, G. S., KHOTENOVSKAYA, T. S., DVORKIN, O. E.

"Fast Superhigh Frequency Switch"

USSR Author's Certificate No 253880, Filed 23 Jul 69, Published 3 Mar 70
(from RZh-Radiotekhnika, No 9, Sep 70, Abstract No 9B150P)

Translation: The proposed superhigh frequency switch is executed in the form of a T-junction on two arms of which varactor diodes with tuning loops are installed. In order to expand the operating frequency band, the external voltage is fed out of phase to two groups of diodes installed on each arm of the switch. The diodes of the first group are tuned to series resonance with a negative bias on the lower frequencies of the operating range, and the diodes of the second group, with positive bias on the upper frequencies of the operating range. There is one illustration.

1/1

USSR

UDC 624.131.551.1+624.154

STAVNITSER, L. R., SHEKHTER, O. YA.

"Forced Horizontal Oscillations of Piles Under Seismic Wave Action"

Moscow, Osnovaniya, fundamenty i mekhanika gruntov, No. 5, 1971, pp 19-23

Abstract: Bending oscillations of a cylindrical pile bearing a mass on the upper end is investigated for the case when stationary longitudinal waves are propagating in a horizontal direction. It is assumed that oscillations of piles placed in the same group occur with the same phase since the distances between them are small as compared with the seismic wavelengths. To obtain an approximate solution, the authors therefore investigate the motion of one pile together with the part of the load imparted to it from the foundation structures. This load is assumed to be concentrated on the upper end of the pile. An approximate discrete scheme in the form of a multimass system with elastic bonds is used for a common solution to the equations for wave action and the transverse vibrations of the pile. This makes it possible to obtain particular solutions of the plane dynamic problem of elasticity theory for each horizontal cross section of the pile with subsequent determination of the matrix of the coefficients from the solution of the equations of the transverse vibrations of the pile. Amplitudes and phases

1/2

USSR

STAVNITSER, L. R., SHEKHTER, O. YA., Osnovaniya, fundamenty i mekhanika gruntov, No. 5, 1971, pp 19-23

of the vibrations of the pile, the dynamic pressure of the ground, and diagrams of the dynamic bending moments and transverse forces are then determined as functions of the depth, time, diameter and length of the pile, static vertical load, elastic properties of the ground and the parameters of the seismic waves. Analysis of computer calculations showed that the greatest values of the dynamic pressure of the ground on the pile and of transverse forces and bending moments occur on the upper end of a pile rigidly embedded into grillage. These values drop off sharply with depth and become practically insignificant for the lower two-thirds of the length. Analysis also showed that only the first mode of the oscillations of the pile is achieved under wave action and that resonance relationships are characterized by a single maximum in the region of very low frequencies.

2/2